

GAPVAX
HV
SERIES
 HYDRO - EXCAVATORS

CUSTOM BUILT TO MEET YOUR NEEDS
 STAY UP TO DATE ON SOCIAL MEDIA
 AND GAPVAX.COM



HV33:

- 6 cubic yard usable debris body
- 4,000 CFM/27" Hg
- 600 gallon water tank
- Three ultra-efficient cyclones with 26 long-lasting filter bags
- New boom design extends up to 18' with a 4' downward pivot



HV44:

- 12-1/2 cubic yard Debris Body
- 4,000 CFM/28" Hg
- 400, 550, 750, 1,000 or 1,200 gal. water tank capacities
- Four ultra-efficient cyclones and 30 long-lasting filter bags



HV55:

- 12-1/2 cubic yard Debris Body
- 5,250 CFM/28" Hg
- 400; 550; 750; 1,000; 1,200 or 1,400 gallon water tank capacities
- Five ultra-efficient cyclones and 34 long-lasting filter bags



GAPVAX GULF COAST
 4510 UNDERWOOD RD
 LA PORTE, TX 77571
 281-884-8658



HEADQUARTERS
 575 CENTRAL AVE.
 JOHNSTOWN, PA 15902
 888-442-7829

GAPVAX
HV
SERIES
 HYDRO EXCAVATORS

GAPVAX HV SERIES

HYDRO - EXCAVATORS

Our HV Series Hydro Excavator is designed by operators for operators. Heavy-duty construction and quality components make it ideal for contractors and municipalities alike. Superior wet and dry filtration is the foundation for the entire family of HV products, regardless of whether it's a suck-and-dump HV57 or a multipurpose HV56.

We've paired stability with performance, making the HV the safest and most versatile unit. At first look, you'll notice something different about the debris tank -- It's between the baghouse and cyclones -- Allowing the payload to sit lower to the ground and offering the lowest center of gravity of any hydrovac available. In addition, the unitized water tank and debris body are constructed on a double subframe, significantly reducing frame fatigue and stress cracks over time. The 45° dump angle lets you get in and out of the dumpsite fast and efficiently. Simply put, the GapVax HV Series Hydro Excavator is Versatile, Reliable, and Durable.

ULTRA EFFICIENT CYCLONES & LONG-LASTING FILTER BAGS

FILTRATION:

- Wet or Dry single mode filtration
- Top loading debris tank, 12" stainless steel floatball shutoff, six centrifugal cyclone material separators
- Baghouse with snap-ring type filter bags and heavy-duty galvanized cages



15 CUBIC YARD DEBRIS BODY

DEBRIS BODY:

- Multiple debris body options
- Dump angle at over 45° for fast unloading and easy clean-out
- Full opening tailgate with field-adjustable locks that assure a complete seal



TRUE WET OR DRY OPERATION

WATER SYSTEM:

- 400; 550; 750; 1,000; 1,200; and 1,700 gallon options
- Tri-plex water pump direct-shaft driven via PTO
- Pump flow ranges from 5-40 GPM; 2,000 - 5,800 PSI
- Standard hose reel is 1/2" x 50' (100-200' reel options are available)



5,200 CFM, 28" HG PD BLOWER

VACUUM SYSTEM:

- Positive displacement pump
- 500 HP transfer case with air-shift engagement
- Specifically designed ultra-quiet air injection and discharge silencers

OTHER FEATURES INCLUDE:

- Noise and vibration dampening mounts on the blower and t-case
- High-efficiency, low maintenance all steel air duct construction with cleanout access
- 20" body access manway
- Full bearing body pivot
- Heavy-duty electric vibrator
- Super heavy-duty rear splash plate
- Body and Tailgate safety props

OPTIONS:

- Vacuum loading boom: 18', 22', or 25' reach from center of truck
- Stainless steel water and/or debris tanks
- Heated cabinets for pump and hose reel
- Water heater: 400,000 BTU or 575,000 BTU
- Hydrostatically driven water pump
- Water recirculation systems
- Glycol injection
- Liquid level load indicator
- Various toolboxes, tube racks, and tube tray options
- Auxiliary lift axles
- Auger unloading system
- Body pressurization system
- Various lighting options
- Remote pendant and wireless controls

*See website for complete listing
gapvax.com



*SPECS SUBJECT TO CHANGE WITHOUT NOTICE

VERSATILE.

RELIABLE.

DURABLE.